



2139

RFID Printer Applicator

The Label-Aire[®] Model 2139 RFID Printer Applicator brings RFID technology to your operation and keeps you ahead of your competition.

The Model 2139 RFID Printer Applicator can thermal transfer or direct transfer (via model 3115 Wipe-On applicator) encoded RFID tags around any corner utilizing our patented vacuum air drum. The 2139's advanced RFID features include EPC, Class 0, Class 0+, Class 1, Gen 2 RFID tag encoding, fully integrated UHF/EPC print-and-apply technology, user friendly Label-Aire RFID tag formatting software, and an innovative Tag Rejecter mechanism. The 2139 RFID's sturdy swing arm can be configured for cartons or pallets labeling any two adjacent side panels. The heavy duty H-frame mounting stand can be bolted to the floor for added stability.

Specifications

Dimensions: Height: 66" (1676 mm), Width: 46.5" (1181 mm), Length: 62.75" (1594 mm)

Weight: 500 lbs. (227 kg)

Standard Label Dimensions: Label Width: Up to 8.8" (224 mm) Label Length: Up to 24" (610 mm)

Dispense Speed: Up to 12" (305 mm) per second depending on printer and label size

Label Placement Accuracy: Up to +/- 1/32" (0.8 mm)

Electrical: 115 Volts AC 60 Hz 5 Amps., 220 Volts AC 50 Hz

Air (as needed): 4 cfm at 60 psi for most applications

Options: Compatible with all O.E.M. RFID printers

Headquarters

550 Burning Tree Road
Fullerton, CA 92833 USA

o 714.441.0700
f 714.526.0300
e info@label-aire.com
w www.label-aire.com

Europe

Sjællandsvej 27A
DK-9500 Hobro, Denmark

o +45 9657 0063
f +45 9657 0064
e info@label-aire-as.com
w www.label-aire-as.com

Distributed by:

MPI Label Systems
450 Courtney Rd.
Sebring, OH 44657
Ph: 800.837.2134
www.mpilabels.com
info@mpilabels.com