


Model 3155



3155 Wipe-On

Primary Applicator


3155 Wipe-On Specifications

The Label-Aire® Model 3155 makes labeling easier and faster...making you more profitable.

The Model 3155 Wipe-On labeler delivers on its promise of speed, accuracy, and ease of use. And that translates into lower operating costs and increased productivity for your business.

Speeds up to 5,000 inches (12,700 cm) of web per minute make the Model 3155 an ideal choice for demanding applications requiring high speed and precision. Advanced features include Automatic Speed Following (ASF) which allows product surface profiling, ensuring wrinkle-free labeling on even the most difficult product shapes and label materials (optional encoder required). Zero Downtime Labeling allows your production to continue without costly interruptions. Product/label queuing and missing label compensation virtually eliminate unlabeled products or missing lot and expiration codes.

Put this high-speed wipe-on pressure-sensitive technology to work for you all day, every day. The Model 3155 Wipe-On labeler is built to meticulous quality standards and designed to withstand the most intense operation.



Dimensions:

Height: 28.6" (726 mm)
 Length: 26.6" (676 mm)
 Width: 31.4" (798 mm)

Weight:

Approx. 170 lbs. (81 kg)

Standard Label Dimensions:

Label Width: Up to 7.13" (181 mm)
 Label Length: 5" (13 mm)

Dispense Speed:

5,000" (12,700 cm) of web per minute

Label Placement Accuracy:

Up to +/- 1/64" (.4 mm)

Electrical:

115 Volts AC 60 Hz 5 Amps.
 220 Volts AC 50 Hz optional

Options:

Encoder kit for Automatic Speed Following
 Zero Downtime Labeling
 Hot stamp imprinter
 Clear label sensor
 Model 2700 T-Base stand
Consult factory for additional options.

3155 Wipe-On Advanced Features

Automatic setup	Includes multiple programmable label pages for easy changeovers to different label sizes.
Stepper motor drive	For precise starting/stopping, increased reliability, wider range speed variability, and lower maintenance.
R3 digital display	Select from five languages (English, French, German, Italian, Spanish), domestic or CE (European) configurations, standard/metric unit display and detailed alarm messages. Can rotate 360°
Automatic Speed Following (ASF)	Labels are accurately applied even through extreme changes in product line speed.
Quick-action collapsible rewind	Allows easy removal of scrap liner.



Headquarters

550 Burning Tree Road
 Fullerton, CA 92833 USA

o 714.441.0700
 f 714.526.0300
 e info@label-aire.com
 w www.label-aire.com

Europe

Sjaellandsvej 27A
 DK-9500 Hobro, Denmark

o +45 9657 0063
 f +45 9657 0064
 e info@label-aire.com
 w www.label-aire.com

Distributed by:

MPI Label Systems
 450 Courtney Rd.
 Sebring, OH 44672
 Ph: 800.837.2134
 www.mpilabels.com
 info@mpilabels.com