

Distributed by:  
MPI Label Systems  
Ph: 800.837.2134  
www.mpilabels.com  
info@mpilabel.com

# 3800i Industrial Linear Imager



## Overview

The 3800i handheld industrial image readers are the first industrial class readers to bring you Hand Held Products industry-leading image technology. This technology allows you to read bar codes at ranges up to 82 inches (208 cm). In real world applications, this extended read range means less climbing and reaching, and more operator productivity.

Based on the proprietary image technology, the 3800i picks up your bar code image and processes its content 270 times per second. In a fraction of a second, the Hand Held Products digital image processor quickly and easily determines the data content and sends it to your host computer. This proprietary technology quickly and securely identifies poor quality symbols, and still delivers snappy performance.

We are so confident the 3800i image reader will withstand your industrial applications that we have backed it by a solid warranty. Every 3800i comes to you with a 3 year warranty against defects. Shock absorbing rubber overmold on the case and a sealed optics module ensure this device will survive dozens of 6.5 foot (2 meter) drops to concrete. Although we do not expect you to treat your reader this way, we know it will survive many years of accidental abuse.

Your industrial applications often take you into environments that challenge many devices. Your loading dock has extreme temperature variations, dirt, dust, and rain that will stress many bar code scanners. The 3800i is environmentally sealed to an IP54 rating, which prevents dust and water from entering the units and degrading performance. Sometimes you need to use this device outdoors during winter or other freezing temperature conditions. This imager withstands applications that subject it to constant -22°F (-30° C) temperatures and still survives.

For reading in applications that exhibit high ambient light, the 3800i can be ordered with an aiming beam, which offers true point and shoot performance without moving laser optics. This option allows the operator to reliably find and scan the code.

## Features

- **Superior Read Range:** Imaging technology now extends the performance range out to 82 inches (208 cm) on linear codes. Long range reading performance eliminates the need to reach and climb to scan codes.
- **Fast and Aggressive Decode:** Even on poorly printed or damaged codes, the 270 scans per second digital image logic is over 6 times faster than other technologies. Spend less time trying to re-scan poor codes and speed up the work process.
- **Rugged Packaging:** An impact absorbing, shock resistant housing withstands fifty 6.5 foot (2 meter) drops, and is sealed to prevent dust, moisture, and other contaminants from entering the scanner. Designed to survive the most demanding industrial applications.
- **Durable:** There are no moving parts to wear out and Hand Held Products backs this with an industry-leading 3 year warranty. Reliable performance year after year with no downtime.
- **Easy to Use:** True point and shoot handheld ergonomics easily fits oversized gloved hands. Intuitive aiming means operators will become productive quickly.

# 3800i Specifications

Performance		Ranges for the 3800i	
<b>Illumination:</b>	630 nM Visible Red LED	<i>Narrow Width</i>	<i>Depth of Field (300 Lux Lighting)</i>
<b>Receiving Device:</b>	3648 element linear imager	7.5 mil	6.5 - 15 in. (16.5 - 38 cm)
<b>Reading Width:</b>	15 mil. code, 15 in. (38.1 cm) from nose, 10 in. (25.4 cm) wide	100% UPC	2.5 - 28 in. (6.4 - 71 cm)
<b>Resolution:</b>	7.5 mil. at 9 in. (22.9 cm) distance	15 mil	2.5 - 31 in. (6.4 - 78.7 cm)
<b>Skew Angle:</b>	+65°	20 mil	1.5 - 42 in. (3.8 - 107 cm)
<b>Pitch Angle:</b>	+65°	55 mil	4.0 - 82 in. (10.2 - 208 cm)
<b>Horizontal Velocity:</b>	2 in. (5.1 cm) per second		
<b>Minimum Symbol Contrast:</b>	20%		
<b>Scan Rate:</b>	Up to 270 scans per second		
<b>Decode Rate:</b>	270 decodes per second		

## Mechanical/Electrical

<b>Dimensions</b>	<u>without aimer</u>	<u>with aimer*</u>
<b>Length:</b>	5.3 in. (13.5 cm)	5.3 in. (13.5 cm)
<b>Height:</b>	6.4 in. (16.3 cm)	6.5 in. (16.5 cm)
<b>Width:</b>	3.2 in. (8.1 cm)	3.2 in. (8.1 cm)
<b>Weight:</b>	7.5 oz. (213 g)	8.4 oz. (238 g)
<b>Housing:</b>	UL 94V0 grade	
<b>Power Requirements:</b>	4.5 - 14Vdc at scanner	
<b>Current Draw (maximum):</b>	<u>Input</u>	<u>Scanning</u> <u>Idle</u>
	5V	235mA      68mA
	12V	142mA      49mA


## Power Supply

<b>Noise Rejection:</b>	Maximum 100mV peak to peak, 10 to 100 kHz
-------------------------	---

## Environmental

<b>Operating Temperature:</b>	-22°F to +122°F (-30°C to +50°C)
<b>Storage Temperature:</b>	-40°F to +140°F (-40°C to +60°C)
<b>Humidity:</b>	0 to 95%, non-condensing
<b>Sealing:</b>	IP54 (water and dust resistant)
<b>Mechanical Shock:</b>	Operational after 50 drops from 6.5 ft. (2 m) to concrete
<b>Ambient Illumination:</b>	0 - 70,000 lux
<b>ESD Protection:</b>	Functional after 15kV discharge
<b>LED Classification:</b>	Class 1 under EN60825-01
<b>Laser Classification</b>	Class 2 under 21 CFR 1040.10 and 1040.11
<b>Aimer Beam only*:</b>	1mW max output, 650 nM, EN60825-1: 1994+A11+A2
<b>Vibration:</b>	Withstands 5G peak from 22 to 300 Hz
<b>Agency:</b>	FCC Class B, CE EMC Class B, CE Low Voltage Directive, UL, cUL listed, TÜV
<b>MTBF:</b>	per MIL-HDBK-217F Ground Benign exceeds 100,000 hours without aimer, 91,000 hours with aimer
<b>Symbologies:</b>	Codabar, Code 39 including PARAF, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, China Post, GS1 DataBar, and ISBT 128 Concatenation (requires a paid license).
<b>Interfaces:</b>	All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, TTL level RS-232, TTL level Serial Wedge, USB, wand emulation, HHLC non-decoded laser compatible, True RS-232, IBM 468x, and IBM469x.
<b>Warranty:</b>	Three-year factory warranty.

\*Not available in Europe; non-RoHS compliant



## Worldwide Offices

### NORTH AMERICA

Skaneateles Falls, NY  
Tel: +1 315 685 8945  
or, in North America:  
+1 800 582 4263  
napresales@handheld.com

### Carolinas

Tel: +1 803 835 8000  
or, in North America:  
+1 800 582 4263  
napresales@handheld.com

### ASIA AND THE PACIFIC RIM

Hong Kong  
Tel: +852 2511 3050  
appresales@handheld.com

### Japan

Tel: +813 5770 6312  
appresales@handheld.com

### Shanghai

Tel: +86 21 6361 3818  
appresales@handheld.com

### Malaysia

Tel: +603-6201 9020  
appresales@handheld.com

### LATIN AMERICA

Naples, Florida  
Tel: +1 239 263 7600  
lapresales@handheld.com

### Rio De Janeiro

Tel: +55 21 2178 0500  
lapresales@handheld.com

### Mexico

Tel: +52 55 5203 2100  
lapresales@handheld.com

### EUROPE, MIDDLE EAST, AND AFRICA

Europe  
Tel: +31 (0) 40 29 01 600  
eusales@handheld.com

### United Kingdom

Tel: +44 (0) 1 925 240055  
eusales@handheld.com

### Italy

Tel: +39 02 7254 6754  
Info.italy@handheld.com

### France

Tel: +33 (0) 1 41 158220  
Info.france@handheld.com

### Germany

Tel: +49 (0) 7 477 151377  
Info.germany@handheld.com

### Spain

Tel: +34 93 228 78 68  
Info.spain@handheld.com



Hand Held Products, Inc., ("Hand Held Products")®1999-2007. All rights reserved. Printed in the U.S.A. Web Site Address: www.handheld.com  
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.