



# Zebra® 110PAX4™ 170PAX4™



## **PAX4™ Print Engines Deliver Superior Performance and Reliability**

The 110PAX4 and the 170PAX4 print engines are the performance leaders in mission-critical print-and-apply applications. With increased throughput and enhanced connectivity, including wireless and Ethernet, along with all-metal construction and outstanding print quality, PAX4 print engines deliver outstanding value, reliability, and durability.

## **Better Than Ever for High-Volume Needs**

With improved serviceability, faster first-label-out time, and a fully functional real-time clock, the PAX4 print engines deliver what it takes to make print-and-apply solutions super performers. European voltage requirements are now met with the 28V I/O option.

## **Real-time Connectivity and Control**

Reduce downtime and increase productivity. Using advanced ZebraLink™ Solutions, PAX4 print engines offer instant status alert messages and centralized control, allowing you to troubleshoot quickly and keep production lines moving.

## **Wireless Communications**

When equipped with ZebraNet® Wireless Plus, PAX4 supports the latest wireless security and authentication protocols.



**Designed for high-speed, high-throughput applications, both the 110PAX4 (for 4-inch printing) and the 170PAX4 (for print widths up to 6 inches wide) are ideal for print/apply systems including:**

- Mission-critical industrial applications
- High-volume product, carton, case, and pallet labeling
- Packaging



# Specifications at a Glance\*

## 110PAX4

### Print Specifications

#### Print Width

4.1"/104 mm

#### Print Length

Maximum non-continuous media: 39"/990 mm

Maximum continuous media: 100"/2540 mm

### Physical Characteristics

- Width: 9.6"/245 mm
- Height: 11.8"/300 mm
- Depth: 16.4"/417 mm
- Weight: 36.5 lbs./15.6 kg

### Media Characteristics

#### Media Width (label and liner)

0.625"/16 mm to 4.5"/114 mm

#### Media Thickness (label and liner)

0.0058"/0.148 mm to 0.010"/0.254 mm

#### Media Types

Continuous, die-cut or black mark

### Ribbon Characteristics

#### Outside Diameter

4.0"/101.6 mm O.D

#### Standard Length

2,955/900 m

#### Ratio

Ribbon is recommended to be at least as wide as media

#### Ribbon Setup

Ribbon wound coated-side out

#### Core I.D.

1.0"/25.4 mm I.D. core

## 170PAX4

### Printer Specifications

#### Print Width

6.6"/168 mm

#### Print Length

Maximum non-continuous media: 39"/990 mm

Maximum continuous media: 150"/3810 mm

### Physical Characteristics

- Width: 9.6"/245 mm
- Height: 11.8"/300 mm
- Depth: 18.3"/465 mm
- Weight: 35.5 lbs./16.1 kg

### Media Characteristics

#### Media Width (label and liner)

3.0"/76 mm to 7.1"/180 mm

#### Media Thickness (label and liner)

.003"/.076 mm to .012"/305 mm

#### Media Types

Continuous, die-cut or black mark

### Ribbon Characteristics

#### Outside Diameter

4.0"/101.6 mm O.D

#### Standard Length

2,955/900 m

### Ratio

Ribbon is recommended to be at least as wide as media

### Ribbon Setup

Ribbon wound coated-side out

### Core I.D.

1.0"/25.4 mm I.D. core

### Standard Features

- Resolution:
  - 203 dpi/8 dots per mm;
  - 300 dpi/12 dots per mm
- Memory: 10 MB DRAM; 2 MB non-volatile Flash
- Print methods: Thermal transfer or direct thermal
- Print Speed: 12"/305 mm per second (203 dpi)  
8"/203 mm per second (300 dpi)
- Media Sensors: Transmissive and reflective
- Orientation: Right-hand or left-hand
- Industrial all-metal construction
- 10 MB DRAM
- 2 MB non-volatile Flash memory
- Applicator interface
- Multilingual backlit LCD
- Enhanced Alert notification—monitors
- printhead condition
- Multi-level Element Energy Equalizer™ (E<sup>3</sup>) for superior print quality
- 32-bit 133 MHz RISC processor
- Zebra printer driver for Windows® 3.X and Windows 95/98/NT/2000
- Real-time clock
- XML-Enabled printing

### Operating Characteristics

#### Environmental (Thermal Transfer)

- Operating Temp.
  - 40° F/5° C to 104° F/40° C
- Storage Temp.
  - 40° F/-40° C to 160° F/71° C
- Operating Humidity
  - 20% to 95% non-condensing R.H.
- Storage Humidity
  - 5% to 95% non-condensing R.H.

#### Electrical

Universal power supply with power-factor correction 90-264 VAC, 48-62 Hz

#### Agency Approvals

UL-60950 3rd edition, CAN/CSA-C22.2 No 60950-00 3rd edition, FCC part 15 - Class A, ICES-003, EN60950, EN55022-Class A, EN61000-6-2, VCCI, CCC

### Related Products

#### Options and Accessories

- PCMCIA cards
- CompactFlash® cards
- Linear PCMCIA cards available 8 MB and 32 MB
- 64 MB On-Board Linear Flash Memory
- RFID Ready (110PAX4 only)
- WGLA through Swiss 721
- Firmware support for downloadable TrueType™ fonts
- PC memory card
- Additional fonts available

### ZebraLink Solutions

#### Software

- ZebraDesigner™ Pro
- ZebraDesigner for XML
- ZebraNet™ Bridge Enterprise
- ZebraNet Utilities v 7.0
- Zebra Universal Driver
- ZBI-Developer™

#### Networking

- ZebraNet® 10/100 Print Server
- ZebraNet Wireless Plus

#### Firmware

- ZPL® II
- Global Printing
- XML-Enabled printing
- APL-™/APL-D™ (Contact Zebra Development Services for additional details)
- Web View
- Alert
- ZBI 2.0™

### Communications and Interface Capabilities

- High-speed bi-directional parallel interface, Centronics® compatible.
- High serial interfaces: RS-232C and RS422 with DB9F connector
- RS-485 multi-drop capability
- Configured baud rate (110 to 57.6 kB), parity, data bits, and stop bits
- Applicator interface with DB15F connector

### Bar Code Symbolologies

#### Linear Bar Codes

Codabar, Code 11, Code 39, code 93, Code 128 with subsets A/B/C and UCC Case codes, EAN-8, EAN-13, Industrial 2-of-5, Interleaved 2-of-5, IBST-128, Logmars, MSI, Planet Code, Plessey, POSTNET, Standard 2-of-5, UPC-A, UPC-E, UPC and EAN 2 or 5 digit extensions

#### 2-Dimensional

Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF, PDF417, QR Code and TLC 39, Aztec

### Fonts and Graphics

#### Fonts and Character Sets

- Bitmap fonts A through H and GS symbols are expandable up to 10 times, height and width independent
- Smooth scalable font Ø (CG Triumvirate™ Bold Condensed) is expandable dot-by-dot, height and width independent
- Sets: IBM® Code Page 850 International Characters
- Contains UFST® from Monotype Imaging, Inc.

#### Graphic Features

Supports user-defined fonts and graphics— including custom logos

\* Specifications subject to change without notice. ©2010 ZIH Corp. ZebraLink, ZebraNet, Element Energy Equalizer, E<sup>3</sup>, ZBI 2.0, ZBI-Developer, ZebraDesigner, and all product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic, ZebraNet, ZPL and ZPL II are registered trademarks of ZIH Corp. All rights reserved. CompactFlash is a registered trademark of SanDisk Corporation. TrueType is a trademark of Apple Computer, Inc. Centronics is a registered trademark of Centronics Data Computer Corporation. Windows is a trademark of Microsoft Corporation. CG Triumvirate is a trademark of Monotype Imaging, Inc. and may be registered in certain jurisdictions. IBM is a trademark or registered trademark of International Business Machines Corporation in the United States, other countries, or both. UFST is a registered trademark of Monotype Imaging, Inc. Unicode is a trademark of Unicode, Inc. All other trademarks are the property of their respective owners



www.zebra.com

#### Corporate Headquarters

+1 800 423 0442

E-mail: inquiry4@zebra.com

#### Locations

USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin Europe: France, Germany, Italy, Netherlands, Poland, Spain, Sweden

United Kingdom Asia Pacific: Australia, China, India, Japan, Portugal, South Korea Latin America: Argentina, Brazil, Florida (USA), Mexico GSA#: GS-35F-0268N

Africa/Middle East: Russia, South Africa, United Arab Emirates

#### Asia-Pacific Headquarters

+65 6858 0722

E-mail: apacchannelmarketing@zebra.com

#### EMEA Headquarters

+44 (0)1628 556000

E-mail: mseurope@zebra.com

#### Latin America Headquarters

+1 847 955 2283

E-mail: inquiry4@zebra.com

P1028475 R16 (12/10)